UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/553,790	10/19/2005	Francesco Pessolano	NL030397US1	4003

65913   7590   11/25/2008

NXP, B.V.
NXP INTELLECTUAL PROPERTY DEPARTMENT
M/S41-SJ
1109 MCKAY DRIVE
SAN JOSE, CA 95131

EXAMINER
KING, JOHN B

ART UNIT	PAPER NUMBER
4148	

NOTIFICATION DATE	DELIVERY MODE
11/25/2008	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

ip.department.us@nxp.com

	Application No.	Applicant(s)
Office Action Summary	10/553,790	PESSOLANO, FRANCESCO
	Examiner	Art Unit
	JOHN B. KING	4148

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>19 October 2005</u>.
2a)☐ This action is **FINAL**.   2b)☒ This action is non-final.
3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) <u>1-7</u> is/are pending in the application.
    4a) Of the above claim(s) _____ is/are withdrawn from consideration.
5)☐ Claim(s) _____ is/are allowed.
6)☒ Claim(s) <u>1-7</u> is/are rejected.
7)☐ Claim(s) _____ is/are objected to.
8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☒ The specification is objected to by the Examiner.
10)☒ The drawing(s) filed on <u>19 October 2005</u> is/are: a)☒ accepted or b)☐ objected to by the Examiner.
    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
    a)☒ All   b)☐ Some * c)☐ None of:
      1.☒ Certified copies of the priority documents have been received.
      2.☐ Certified copies of the priority documents have been received in Application No. _____.
      3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☒ Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date <u>10-19-2005</u>.
4) ☐ Interview Summary (PTO-413) Paper No(s)/Mail Date. _____ .
5) ☐ Notice of Informal Patent Application
6) ☐ Other: _____ .

DETAILED ACTION

1.   The instant application having Application No. 10553790 filed on October 19,

2005 is presented for examination by the examiner.

Oath/Declaration

2.   The applicant's oath/declaration has been reviewed by the examiner and is found

to conform to the requirements prescribed in **37 C.F.R. 1.63.**

Information Disclosure Statement

3.   The information disclosure statement (IDS) submitted on 10/19/2005 is in

compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure

statement is being considered by the examiner.

Drawings

4.   The applicant's drawings submitted are acceptable for examination purposes.

Specification

5.   The following guidelines illustrate the preferred layout for the specification of a

utility application. These guidelines are suggested for the applicant's use.

Arrangement of the Specification

As provided in 37 CFR 1.77(b), the specification of a utility application should

include the following sections in order. Each of the lettered items should appear in

upper case, without underlining or bold type, as a section heading. If no text follows the

section heading, the phrase "Not Applicable" should follow the section heading:

(a) TITLE OF THE INVENTION.
(b) CROSS-REFERENCE TO RELATED APPLICATIONS.
(c) STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR
      DEVELOPMENT.
(d) THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT.
(e) INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A
      COMPACT DISC.

(f) BACKGROUND OF THE INVENTION.
      (1) Field of the Invention.
      (2) Description of Related Art including information disclosed under 37
      CFR 1.97 and 1.98.
(g) BRIEF SUMMARY OF THE INVENTION.
(h) BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S).
(i) DETAILED DESCRIPTION OF THE INVENTION.
(j) CLAIM OR CLAIMS (commencing on a separate sheet).
(k) ABSTRACT OF THE DISCLOSURE (commencing on a separate sheet).
(l) SEQUENCE LISTING (See MPEP § 2424 and 37 CFR 1.821-1.825. A
      "Sequence Listing" is required on paper if the application discloses a
      nucleotide or amino acid sequence as defined in 37 CFR 1.821(a) and if
      the required "Sequence Listing" is not submitted as an electronic
      document on compact disc).

Claim Rejections - 35 USC § 112

6.   The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly
claiming the subject matter which the applicant regards as his invention.

7.   **Claims 3 and 5** are rejected under 35 U.S.C. 112, second paragraph, as being

indefinite for failing to particularly point out and distinctly claim the subject matter which

applicant regards as the invention.

8.   **Claim 3** recites the limitation "the combinatorial circuits" in lines 2 and 7. There

is insufficient antecedent basis for this limitation in the claim. For the purposes of

examination of this application the examiner will interpret the terms "combinatorial

circuits" and "combinatorial logic circuits" as the same.

9.   **Claim 3** recites the limitation "the electronic circuit" in line 4. There is insufficient

antecedent basis for this limitation in the claim. For the purposes of examination of this

application the examiner will interpret the terms "electronic circuit" and "electronic circuit

device" as the same.

10.   **Claim 5** recites the limitation "the electronic circuit" in line 5. There is insufficient

antecedent basis for this limitation in the claim. For the purposes of examination of this

application the examiner will interpret the terms "electronic circuit" and "electronic circuit

device" as the same.

Claim Rejections - 35 USC § 102

11.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that

form the basis for the rejections under this section made in this Office action:

> A person shall be entitled to a patent unless –
>
> (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

12.   **Claims 1, 5 and 7** are rejected under 35 U.S.C. 102(b) as being anticipated by

Thüringer et al. (US 6498404 B1), published December 24, 2002 hereinafter referred to

as Thüringer.

As per claim 1, Thüringer discloses an electronic circuit device for executing

operations dependent on secret information, the electronic circuit device, comprising:

power supply connections **(col. 1 lines 28-32 and col. 2 lines 28-30, Thüringer**

teaches the use of power supplies.); a processing unit **[circuit arrangement]**

comprising a plurality of processing circuits for use in execution respective parts of the

operations dependent on the secret information **(col. 1 lines 45-52, Thüringer teaches**

a circuit arrangement for performing security-relevant operations where the

security-relevant operations involve processing secret information as indicated in

col. 2 lines 62-67 through col. 3 lines 1-6. Thüringer, Figure 2, discloses a plurality

of processing circuits such as the AND gates.), the processing circuits being fed

from the power supply connections **(Figure 2, Thüringer teaches having a set of AND**

gates. It is inherent that the AND gates are connected to the power supply in

order for the circuit to work.); an activity monitor circuit coupled to receive pairs of

processing signals coming into and out of respective ones of the processing circuits

(Figure 2, Thüringer teaches a circuit that takes in a pair of signals and then

outputs a pair of signals after processing. Thüringer, col. 2 lines 39-45, discloses

the inputting and outputting of Figure 2.), the activity monitor circuit being arranged

to derive activity information derived from each pair of processing signals **(col. 2 lines**

47-60, Thüringer teaches the circuit determining if the incoming logic signals are

high or low.), and to derive from the activity information a combined activity signal

indicative of a sum of power supply currents that will be consumed by the processing

circuits dependent on the processing signals **(col. 1 lines 46-65, Thüringer teaches**

the load circuit being controlled by what happens in the other parts of the circuit

device. Thüringer, col. 1 lines 46-52, teaches that the load circuit produces a

current to be complementary to the rest of the circuit. Therefore, the load current

is being added to the current that the remainder of the circuit is using to prevent

third parties from determining the secret information by measuring the power

consumed by the device.); a current drawing circuit connected to the power supply

connections and controlled by the activity monitor circuit to draw a cloaking current

controlled by the combined activity signal **(col. 1 lines 28-38, Thüringer teaches**

having a load circuit connected to the power supply to mask the measurable

power consumption. Thüringer, col. 1 lines 46-65, teaches the load circuit being

complementary to the other parts of the circuit. The AND gates process the

incoming signals to generate the complement to be used to control the load

circuit.), so that power supply current variations dependent on the secret information

are cloaked in a combination of the cloaking current and current drawn by the

processing circuits **(col. 1 lines 46-52, Thüringer teaches that the load circuit**

produces a current to be complementary to the rest of the circuit. Therefore, the

load current is being added to the current that the remainder of the circuit is

using.)

As per claim 5, Thüringer discloses an electronic circuit device according to claim

1 **[See rejection to claim 1 above]**, having a trigger input coupled to the current

drawing circuit **(Thüringer, Figure 3 and col. 3 lines 17-23, teaches having a voltage**

signal, V, connected to the switching transistors to control the load resistors.),

arranged to enable drawing of the cloaking current only upon receiving a trigger signal

that triggers or accompanies execution of a secret information dependent process in the

electronic circuit **(Thüringer, Figure 3 and col. 3 lines 17-23, teaches having**

transistors connected to the load circuit resistors. Therefore, the load current will

only be drawn when the transistors are switched on, when the voltage V signal is

high.)

As per claim 7, Thüringer discloses a method of executing operations dependent

on secret information in an electronic circuit, the method comprising: supplying power

supply current to processing circuits **(col. 1 lines 28-32 and col. 2 lines 28-30,**

Thüringer teaches the use of power supplies.); executing respective parts of

operations that dependent on the secret information using the processing circuits **(col. 1**

lines 45-52, Thüringer teaches a circuit arrangement for performing security-

relevant operations where the security-relevant operations involve processing

secret information as indicated in col. 2 lines 62-67 through col. 3 lines 1-6.);

receiving pairs of processing signals coming into and out of respective ones of the

processing circuits **(Figure 2, Thüringer teaches a circuit that takes in a pair of**

signals and then outputs a pair of signals after processing. Thüringer, col. 2 lines

39-45, disclose the inputting and outputting of Figure 2.); deriving activity

information from each pair of processing signals **(col. 2 lines 47-60, Thüringer**

teaches the circuit determining if the incoming logic signals are high or low.),

deriving from the activity information a combined activity signal indicative of a sum of

power supply currents that will be consumed by the processing circuits dependent on

the processing signals **(col. 1 lines 46-65, Thüringer teaches the load circuit being controlled by what happens in the other parts of the circuit device. Thüringer, col. 1 lines 46-52, Thüringer teaches that the load circuit produces a current to be complementary to the rest of the circuit. Therefore, the load current is being added to the current that the remainder of the circuit is using. Thüringer, col. 1 lines 33-37, also teaches that the measure power consumption will be the combination of the power drawn by the data processing device and the excess power drawn by the load circuit.)**; drawing a cloaking current controlled by the combined activity signal **(col. 1 lines 28-38, Thüringer teaches having a load circuit connected to the power supply to mask the measurable power consumption. Thüringer, col. 1 lines 46-65, teaches the load circuit being complementary to the other parts of the circuit. The AND gates process the incoming signals to generate the complement to be used to control the load circuit.)**, and combining that cloaking current with current drawn by the processing circuits so that power supply current variations dependent on the secret information are cloaked in the combination of the cloaking current and current drawn by the processing circuits **(col. 1 lines 46-52, Thüringer teaches that the load circuit produces a current to be complementary to the rest of the circuit. Therefore, the load current is being added to the current that the remainder of the circuit is using.)**

falseofffalse

falsefalsefalsefalsefalsefalseoffofffalse

---

3 lines 32-34, Thüringer teaches the use of a synchronous circuit, which involves a clock.)

Furthermore, Patterson discloses the processing unit comprises a clock circuit **(pages 134-135, Patterson teaches having a clock.)**, combinatorial logic circuits and registers clocked by the clock circuit and connected between respective parts of the combinatorial logic circuits **(Figure 3.4, Patterson teaches a processor instruction datapath being pipelined and adding a set of registers between each pair of pipeline stages. Patterson also teaches that every pipeline stage is active on each clock cycle. Therefore, the registers must also be controlled by the clock because the values in the registers can change after each pipeline stage.)**, the pairs of processing signals comprising pairs of input and output signals of the registers **(Figure 3.4, Patterson teaches a set of registers. Each register has a set of signals coming into and going out of the register.)**, the current drawing circuit being arranged to adjust a value of the cloaking current dependent on the activity of the registers at instants synchronized by the clock circuit **(Thüringer, Figure 3 and col. 3 lines 17-25, teaches using a computing element, and monitoring this computing element, to generate the complementary loading current used to mask the measurable power consumption. It is well know in the art that registers are computing elements. Patterson, pages 134-135, teaches using registers as computing elements.)**

Thüringer and Patterson are analogous art because they are from the same field of endeavor of using computer circuitry to perform a set of instructions.

It would have been obvious to one of ordinary skill in the art at the time of the

invention to modify Thüringer's teachings with the teachings of Patterson because

adding the registers between the different combinatorial logic circuits is helpful to

transfer data from one combinatorial logic circuit to the next **(Patterson, Figure 3.4,**

teaches the use of the pipeline registers.)

As per claim 3, Thüringer in view of Patterson discloses an electronic circuit

device according to claim 2 **[See rejection to claim 2 above]**, organized as a pipe-line

of successive parts of the combinatorial circuits **(Thüringer, Figure 3, teaches the use**

of a pipe-line. The layout of the circuit is such that the output from one set of

circuits is the input into another set of circuits and this constitutes a pipe-line.),

each pair of successive parts coupled via a respective one or respective ones of the

registers **(Patterson, Figure 3.4, teaches a processor instruction datapath being**

pipelined and adding a set of registers between each pair of pipeline stages.), the

electronic circuit **(Thüringer, Figures 1-3, teach an electronic circuit.)**, comprising: a

plurality of activity monitor circuits **(Thüringer, Figures 2-3, teach a set of circuits that**

are used to monitor the activity (logic high or low) of the incoming signals and

generate a load current to mask the measurable power consumption.), each

coupled to receive pairs of input and output signals of the respective one or ones of the

registers between a respective pair of successive parts of the combinatorial circuits

(Figure 3.4, Patterson teaches a set of registers between each pipeline stage.

Each stage in the pipeline is comprised of a set of combinatorial circuits. Each

register has a set of signals coming into and going out of the register.), and to

derive a combined activity signal from the pairs of input output signals **(Thüringer, col.**
2 lines 47-60, teaches the circuit determining if the incoming logic signals are
high or low. Thüringer, col. 1 lines 46-65, also teaches the load circuit being
controlled by at least part of the data processing device. As shown in Thüringer
Figure 3, the signals that are processed by the data processing device are sent to
the circuit arrangement of Figure 2 to generate the complement which is later
used to control the load circuit to mask the measurable power consumption.); a
plurality of current drawing circuits connected to the power supply connections
(Thüringer, Figure 2, discloses a plurality of processing circuits such as the AND
gates. It is inherent that the AND gates are connected to the power supply in
order for the circuit to work.), each controlled by a respective one of the activity
monitor circuits to draw a cloaking current controlled by combined activity signal derived
by that respective one of the activity monitor circuits **(Thüringer, col. 1 lines 46-65,**
teaches the load circuit being controlled by at least part of the data processing
device. As shown in Thüringer Figure 3, the signals that are processed by the
data processing device are sent to the circuit arrangement of Figure 2 to generate
the complement which is later used to control the load circuit to mask the
measurable power consumption.)

As per claim 4, Thüringer in view of Patterson discloses an electronic circuit
device according to claim 3 **[See rejection to claim 3 above]**, arranged to activate the
current drawing circuits in selected clock cycles **(Thüringer, col. 1 lines 28-33 and col.**
1 lines 46-65, teach using a load circuit during security-relevant operations to

mask the measurable power supply. Patterson, page 134, teaches executing

every stage in the pipeline during each clock cycle. Thüringer, col. 3 lines 32-34,

also teaches the use of a clock.), when the corresponding pipe-line stages process

secret information **(Thüringer, col. 1 lines 28-33, teaches using the load circuit to**

mask the measurable power consumption at least during security-relevant

operations where the security-relevant operations involve processing secret

information as indicated in col. 2 lines 62-67 through col. 3 lines 1-6. Patterson,

pages 134-135 and Figure 3.4, teaches the use of pipeline stages.)

15.   **Claim 6** is rejected under 35 U.S.C. 103(a) as being unpatentable over

Thüringer.

As per claim 6, Thüringer discloses an electronic circuit device according to claim

1 **[See rejection to claim 1 above], comprising** a reference current pattern generator,

the current drawing circuit being arranged to adjust the value of the cloaking current so

that the combination of the cloaking current and current drawn by the processing circuits

substantially equals a temporal reference current pattern generated by the reference

current pattern generator **(col. 1 lines 53-55, Thüringer teaches keeping the**

measurable power consumption constant.) The concepts and advantages of

using a reference pattern is well known and expected in the art. For example, U.S.

Patent number US 4212056 describes comparing a detected signal to a reference

current pattern to vary the pulse width in a PWM (Pulse Width Modulation) system

(see col. 6 lines 45-50). Thus, it would have been obvious to one of ordinary skill

in the art at the time of the invention to generate a reference current pattern,

compare the reference current pattern to another current signal, and modify that

current signal to match the reference current pattern because the modified

current signal should always be constant (col. 1 lines 52-55, Thüringer teaches

that the measurable power consumption, in an ideal case, should always be

constant.)

Conclusion

16.   Any inquiry concerning this communication or earlier communications from the

examiner should be directed to JOHN B. KING whose telephone number is (571)270-

7310. The examiner can normally be reached on Mon. - Thur. 7:30 AM - 5:00 PM est..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Thomas Pham can be reached on (571)272-3689. The fax phone number

for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

JBK

/Thomas K Pham/
Supervisory Patent Examiner, Art Unit 4148